



US010124201B2

(12) **United States Patent**
Hopperstad et al.

(10) **Patent No.:** **US 10,124,201 B2**

(45) **Date of Patent:** ***Nov. 13, 2018**

(54) **WALL MOUNTED EXERCISE RACK SYSTEM**

(71) Applicant: **PRX Performance, LLC**, Fargo, ND (US)

(72) Inventors: **Erik S. Hopperstad**, Moorhead, MN (US); **Brian B. Brasch**, Fargo, ND (US)

(73) Assignee: **PRx Performance, LLC**, Fargo, ND (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/005,477**

(22) Filed: **Jun. 11, 2018**

(65) **Prior Publication Data**

US 2018/0290003 A1 Oct. 11, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/846,157, filed on Dec. 18, 2017, now Pat. No. 9,993,678, which is a (Continued)

(51) **Int. Cl.**
A63B 21/00 (2006.01)
A63B 21/068 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A63B 21/00047** (2013.01); **A63B 1/00** (2013.01); **A63B 17/04** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **A63B 21/00047**; **A63B 21/068**; **A63B 21/169**; **A63B 21/16**; **A63B 21/1618**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,104,505 A 7/1914 Holworthy
2,855,200 A 10/1958 Blackman
(Continued)

FOREIGN PATENT DOCUMENTS

DE 4307632 A1 9/1993
GB 2076299 A 12/1981

OTHER PUBLICATIONS

<http://www.roguefitness.com:80/dirty-south-bar.php>; Rogue Fitness Dirty South Bar Website Page; Jan. 23, 2013.

(Continued)


Primary Examiner — Joshua Lee

(74) *Attorney, Agent, or Firm* — Neustel Law Offices

(57) **ABSTRACT**

A retractable wall mounted exercise rack system for providing an exercise rack that may be easily and compactly stored when not in use. The retractable wall mounted exercise rack system generally includes one or more brackets attached to a wall, a pair of support members, and a plurality of arms pivotally extending from the brackets and pivotally connecting to the support members. One or more actuators are connected between the brackets and the arms to assist in lifting the structure into a compact retracted position for storage.

24 Claims, 14 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/594,971, filed on May 15, 2017, now Pat. No. 9,844,691, which is a continuation of application No. 15/357,336, filed on Nov. 21, 2016, now Pat. No. 9,649,525, which is a continuation of application No. 15/230,782, filed on Aug. 8, 2016, now Pat. No. 9,498,670, which is a continuation of application No. 15/149,775, filed on May 9, 2016, now Pat. No. 9,409,048, which is a continuation of application No. 14/682,431, filed on Apr. 9, 2015, now Pat. No. 9,333,387.

(60) Provisional application No. 61/977,435, filed on Apr. 9, 2014.

(51) **Int. Cl.**

A63B 17/04 (2006.01)
A63B 1/00 (2006.01)
A63B 21/078 (2006.01)
A63B 23/035 (2006.01)
A63B 23/04 (2006.01)
A63B 23/12 (2006.01)
A63B 21/06 (2006.01)
A63B 21/16 (2006.01)

(52) **U.S. Cl.**

CPC *A63B 21/068* (2013.01); *A63B 21/078* (2013.01); *A63B 21/169* (2015.10); *A63B 21/4029* (2015.10); *A63B 21/4035* (2015.10); *A63B 23/0405* (2013.01); *A63B 23/1218* (2013.01); *A63B 21/06* (2013.01); *A63B 21/16* (2013.01); *A63B 21/40* (2015.10); *A63B 21/4027* (2015.10); *A63B 21/4033* (2015.10); *A63B 23/035* (2013.01); *A63B 23/04* (2013.01); *A63B 23/12* (2013.01); *A63B 23/1209* (2013.01); *A63B 2023/0411* (2013.01); *A63B 2208/02* (2013.01); *A63B 2208/029* (2013.01); *A63B 2210/00* (2013.01); *A63B 2210/50* (2013.01); *A63B 2210/56* (2013.01); *A63B 2225/09* (2013.01); *A63B 2225/093* (2013.01)

(58) **Field of Classification Search**

CPC A63B 21/1627; A63B 21/1636; A63B 21/1645; A63B 21/1654; A63B 21/1663; A63B 21/1681; A63B 21/072; A63B 21/0724; A63B 21/078; A63B 21/0783; A63B 21/4035; A63B 21/4029; A63B 7/00; A63B 23/1218; A63B 2023/0411; A63B 2208/029; A63B 2210/00; A63B 2210/10; A63B 2210/50; A63B 2210/56; A63B 2210/58; Y10S 248/917; B60R 3/02; A47B 46/00; A47B 46/005; A61G 7/1019; F16M 11/046; F16M 11/10; F16M 2200/063
 USPC 482/38
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,614,097 A 10/1971 Blickman
 3,874,657 A 4/1975 Niebojewski
 3,918,710 A 11/1975 Niebojewski
 4,249,726 A 2/1981 Faust
 4,257,590 A 3/1981 Sullivan
 4,262,901 A 4/1981 Faust

4,286,782 A 9/1981 Fuhrhop
 4,306,715 A 12/1981 Sutherland
 4,358,109 A 11/1982 Schrems
 4,368,884 A 1/1983 Colvin
 4,369,966 A 1/1983 Silberman
 4,396,191 A 8/1983 Metler
 4,527,797 A 7/1985 Slade, Jr.
 4,603,855 A 8/1986 Sebelle
 4,615,524 A 10/1986 Sutherland
 4,621,809 A 11/1986 Pearl
 4,635,934 A 1/1987 Roethke
 4,637,608 A 1/1987 Owens
 4,645,196 A 2/1987 Christie
 4,650,186 A 3/1987 McCreery
 4,729,561 A 3/1988 Desjardins
 4,757,998 A 7/1988 Landin
 4,765,616 A 8/1988 Wolff
 4,773,642 A 9/1988 Cruz
 4,781,374 A 11/1988 Lederman
 4,795,149 A 1/1989 Pearson
 4,804,179 A 2/1989 Murphy
 4,826,153 A 5/1989 Schalip
 4,842,270 A 6/1989 Lange
 4,844,448 A 7/1989 Niznik
 4,861,024 A 8/1989 Lee
 4,861,025 A 8/1989 Rockwell
 4,898,381 A 2/1990 Gordon
 4,907,798 A 3/1990 Burchatz
 4,915,377 A 4/1990 Malnke
 4,919,419 A 4/1990 Houston
 4,927,135 A 5/1990 Nieppola
 4,928,961 A 5/1990 Madden
 4,934,693 A 6/1990 Santoro
 4,936,572 A 6/1990 Desiderio
 4,955,604 A 9/1990 Pogue
 4,958,833 A 9/1990 Stater
 4,960,277 A 10/1990 LaRossa
 4,974,837 A 12/1990 Someya
 4,976,428 A 12/1990 Ghazi
 5,011,141 A 4/1991 Towley, III
 5,046,722 A 9/1991 Antoon
 5,082,259 A 1/1992 Gonzalez
 5,082,260 A 1/1992 Dinelli
 5,098,361 A 3/1992 Danylienko
 5,141,480 A 8/1992 Lennox
 5,151,072 A 9/1992 Cone
 5,184,992 A 2/1993 Banks
 5,242,345 A 9/1993 Mitchell
 5,249,858 A 10/1993 Nusser
 5,281,193 A 1/1994 Colbo, Jr.
 5,306,220 A 4/1994 Kearney
 5,328,428 A 7/1994 Huang
 5,346,448 A 9/1994 Sollo
 5,350,346 A 9/1994 Martinez
 5,456,644 A 10/1995 Hecox
 5,466,204 A 11/1995 Nearing
 5,509,876 A 4/1996 Reyes
 5,551,936 A 9/1996 Parisi
 5,669,859 A 9/1997 Liggett
 5,688,216 A 11/1997 Mauriello
 D390,287 S 2/1998 Hsieh
 5,755,823 A 5/1998 Cleary
 5,779,601 A 7/1998 Ish, III
 5,813,951 A 9/1998 Einsig
 5,882,283 A 3/1999 Stevens
 5,921,897 A 7/1999 Stevens
 5,971,897 A 10/1999 Olson
 6,027,433 A 2/2000 Flynn
 6,073,624 A 6/2000 Laurent
 6,248,048 B1 6/2001 Zuckerman
 6,299,568 B1 10/2001 Prok
 6,328,679 B1 12/2001 Croft
 6,443,877 B1 9/2002 Hoecht
 6,579,213 B1 6/2003 Webber
 6,685,601 B1 2/2004 Knapp
 7,070,546 B1 7/2006 Grasso
 7,338,416 B2 3/2008 Smith
 7,374,516 B2 5/2008 Lundquist
 7,393,309 B2 7/2008 Webber

(56)

References Cited

U.S. PATENT DOCUMENTS

7,455,621	B1	11/2008	Anthony
7,549,950	B1	6/2009	Lundquist
7,635,322	B2	12/2009	Parrilla
7,666,118	B1	2/2010	Anthony
7,699,756	B2	4/2010	Piane, Jr.
8,047,972	B1	11/2011	Dean
8,231,509	B2	7/2012	Lundquist
8,491,449	B2	7/2013	Rogers
8,517,900	B1	8/2013	Britt
8,727,953	B2	5/2014	Drechsler
2004/0092369	A1	5/2004	Slawinski
2008/0276551	A1	11/2008	Thomas
2009/0143203	A1	6/2009	Knapp
2009/0289535	A1	11/2009	Weber
2012/0289384	A1	11/2012	Staten
2013/0257242	A1	10/2013	Bunch
2015/0148197	A1	5/2015	Lentz
2016/0016033	A1	1/2016	Schrag

OTHER PUBLICATIONS

<http://www.roguefitness.com:80/bodyweight-gymnastics/rpg-pullup-system.php>; Rogue Fitness Pull Up & RPG Systems Website Page; Jan. 23, 2013.

<http://www.roguefitness.com:80/rogue-r-3-power-rack.php>; Rogue Fitness R3 Power Rack Website Page; Jan. 11, 2013.

<http://www.roguefitness.com:80/rogue-sm-2-monster-squat-stand.php>; Rogue Fitness SM-2 Monster Squat Stand Website Page; Jan. 27, 2013.

<http://www.roguefitness.com:80/w4-garage-gym.php>; Rogue Fitness W-4 Garage Gym Website Page; Jan. 23, 2013.

<http://www.roguefitness.com:80/x-43m-multi-grip-crossmember.php>; Rogue Fitness X-43 Multi-Grip Crossmember Website Page; Jan. 23, 2013.

<http://www.roguefitness.com/rogue-4-monster-lite-wall-mount>, Monster Lite Wall Mount Webpage from Rogue Fitness; Jan. 1, 2014.

<http://board.crossfit.com/showthread.php?t=86058>; Website for Crossfit Message Board; Feb. 8, 2014.

<http://board.crossfit.com/showthread.php?t=86058>; Pictures from Website for Crossfit Message Board; Feb. 8, 2014.

Pictures of PRX Performance Pull-Up Bar on Central Rig Display at Granite Games; Oct. 5, 2013.

https://www.youtube.com/watch?v=f6bPYbS_2Fw; YouTube Video Equipment Demo Rogue Dirty South Bar; Apr. 26, 2012.

<https://www.youtube.com/watch?v=koAzH91o474>; YouTube Video Matt Chan Talks the Dirty South Bar; Dec. 20, 2012.

2717 Equipment Facebook Posts—Wall Mounted Pull Up and Squat Rack; Mar. 27, 2012.

2717 Equipment Facebook Posts—W-1 Pull Up and Rack; Nov. 8, 2012.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8a




FIG. 8b




FIG. 8c




FIG. 8d




FIG. 9




FIG. 10




FIG. 11

WALL MOUNTED EXERCISE RACK SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation application of U.S. application Ser. No. 15/846,157 filed on Dec. 18, 2017 which issues as U.S. Pat. No. 9,993,678 on Jun. 12, 2018, which is a continuation application of U.S. application Ser. No. 15/594,971 filed on May 15, 2017 now issued as U.S. Pat. No. 9,844,691, which is a continuation application of U.S. application Ser. No. 15/357,336 filed on Nov. 21, 2016 now issued as U.S. Pat. No. 9,649,525, which is a continuation application of U.S. application Ser. No. 15/230,782 filed on Aug. 8, 2016 now issued as U.S. Pat. No. 9,498,670, which is a continuation application of U.S. application Ser. No. 15/149,775 filed on May 9, 2016 now issued as U.S. Pat. No. 9,409,048, which is a continuation of U.S. application Ser. No. 14/682,431 filed on Apr. 9, 2015 now issued as U.S. Pat. No. 9,333,387, which claims priority to U.S. Provisional Application No. 61/977,435 filed Apr. 9, 2014. Each of the aforementioned patent applications, and any applications related thereto, is herein incorporated by reference in their entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable to this application.

BACKGROUND OF THE INVENTION

Field of the Invention

Example embodiments in general relate to exercise equipment and more specifically it relates to a retractable wall mounted exercise rack system for providing an exercise rack that may be easily and compactly stored when not in use.

Description of the Related Art

Any discussion of the related art throughout the specification should in no way be considered as an admission that such related art is widely known or forms part of common general knowledge in the field.

Conventional exercise racks for use in working out with a weighted barbell have been in use for years. Examples of convention exercise racks include squat stands, squat racks, squat cages, power racks and rigs. Conventional exercise racks are used for various types of exercises such as, but not limited to, squatting, bench presses, pull-ups and the like. A conventional exercise rack is comprised of a base, four vertical supports extending upwardly from the base and an upper connecting structure attached to the upper portions of the vertical supports. The vertical supports include spaced apart openings for receiving various types of support brackets (e.g. J-cups) to receive a barbell at various heights. One or more pull-up bars may also be attached to upper portions of the exercise rack allowing the user to perform pull-up exercises on the exercise rack.

One problem with conventional exercise racks is they require a significant amount of space to utilize. Another problem with conventional exercise racks is they are not capable of being compactly stored without disassembling them.

Because of the inherent problems with the related art, there is a need for a new and improved retractable wall mounted exercise rack system for providing an exercise rack that may be easily and compactly stored when not in use.

BRIEF SUMMARY OF THE INVENTION

An example embodiment of the retractable wall mounted exercise rack is directed to an exercise device which includes an upper bracket and a lower bracket attachable to a wall, a pair of support members, and a plurality of arms pivotally extending from the brackets and pivotally connecting to the support members. One or more actuators are connected between the brackets and the arms to assist in lifting the structure into a compact retracted position for storage.

There has thus been outlined, rather broadly, some of the features of the exercise device in order that the detailed description thereof may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the exercise device that will be described hereinafter and that will form the subject matter of the claims appended hereto. In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the exercise device is not limited in its application to the details of construction or to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of the description and should not be regarded as limiting.

BRIEF DESCRIPTION OF THE DRAWINGS

Various other objects, features and attendant advantages of the exercise device will become fully appreciated as the same becomes better understood when considered in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the several views, and wherein:

FIG. 1 is a first front perspective view of the retractable wall mounted exercise rack in the extended position for usage.

FIG. 2 is a first rear perspective view of the retractable wall mounted exercise rack in the extended position.

FIG. 3 is a first front perspective view of the retractable wall mounted exercise rack in the compact retracted position.

FIG. 4 is a first rear perspective view of the retractable wall mounted exercise rack in the compact retracted position.

FIG. 5 is a front view of the retractable wall mounted exercise rack.

FIG. 6 is a rear view of the retractable wall mounted exercise rack.

FIG. 7 is a right side view of the retractable wall mounted exercise rack.

FIG. 8a is a left side view of the retractable wall mounted exercise rack attached to a wall in the extended position for usage with the arms horizontally aligned.

FIG. 8b is a left side view of the retractable wall mounted exercise rack being moved into the retracted position.

FIG. 8c is a left side view of the retractable wall mounted exercise rack in the retracted position for compact storage.

FIG. 8d is a left side view of the retractable wall mounted exercise rack attached to a wall in the extended position for usage with the arms angled downwardly from the wall.

FIG. 9 is a first front perspective view of the retractable wall mounted exercise rack attached to a wall and in the compact retracted position.

FIG. 10 is a top view of the retractable wall mounted exercise rack attached to a wall and in the extended position.

FIG. 11 is a first front perspective view of an alternative embodiment for a retractable squat rack without a pull-up bar.

DETAILED DESCRIPTION OF THE INVENTION

A. Overview.

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, FIGS. 1 through 11 illustrate a retractable wall mounted exercise rack system 10, which comprises an upper bracket 20 and a lower bracket 30 attachable to a wall 14, a pair of support members 40, 50, and a plurality of arms 22, 32 pivotally extending from the brackets 20, 30 and pivotally connecting to the support members 40, 50. One or more actuators 24, 34 are connected between the brackets 20, 30 and the arms 22, 32 to assist in lifting the structure into a compact retracted position for storage. The retractable wall mounted exercise rack may be attached to various building structures such as, but not limited to, the interior or exterior of a building structure, a garage, a gym, a bedroom and the like. It can be appreciated that the retractable wall mounted exercise rack may be utilized with a single rack system with only two support members 40, 50 or a multiple rack system with more than two support members 40, 50.

The retractable wall mounted exercise rack preferably pivots upwardly and downwardly with respect to the wall 14 for compact storage of the invention. However, the retractable wall mounted exercise rack may also pivot from side-to-side with respect to the wall 14 without being elevated with the pivot axis rotated 90 degrees with respect to the pivot axis illustrated in FIGS. 1 through 11 of the drawings. The retractable wall mounted exercise rack may also be pivoted diagonally at various angles with respect to the wall 14. As can be appreciated, the retractable wall mounted exercise rack may pivot with respect to the wall 14 along a horizontal axis (FIGS. 1 through 11), a vertical axis or a diagonal axis. One important feature and function of the retractable wall mounted exercise rack is the ability to move the support members 40, 50 from an extended position where the support members 40, 50 are distally spaced away from the wall 14 (FIG. 8a) to a retracted position that is compact and substantially flush with the wall 14 (FIG. 8c). When in the extended position, the support members 40, 50 are preferably at least 20 inches away from the wall 14 measured from the outside surface of the front of the support members 40, 50 to the surface of the wall 14 to provide sufficient space for a user to perform various types of exercises (e.g. kipping pull-ups, butterfly pull-ups, weighted pull-ups, toes to bar, etc.). When in the retracted position, the support members 40, 50 are preferably less than 4 inches away from the wall 14 measured from the outside surface of the front of the support members 40, 50 to the surface of the wall 14 to provide a compact storage structure that does not interfere with the usage of the surrounding space.

B. Brackets.

The arms 22, 32 are pivotally attached to the wall 14 with one or more brackets 20, 30. Each arm 22, 32 may have its own individual bracket 20, 30 for pivotally attaching to the wall 14. Each of the brackets 20, 30 includes one or more apertures or extended structures that receive a fastener (e.g. a threaded fasteners, lag bolts, lag screws, etc.) that extends into the wall 14 and preferably into a stud within the wall 14 to securely retain the bracket 20, 30.

The apertures extending through the brackets 20, 30 may have various shapes such as circular, oval, slotted and the like. The apertures extending through the brackets 20, 30 are preferably aligned with the distance of conventional frame studs in a wall 14 such as, but not limited to, 16 inch intervals and/or 24 inch intervals. FIG. 8c illustrates the usage of threaded fasteners to secure the brackets 20, 30 to the wall 14.

When attached to the wall 14, the brackets 20, 30 are preferably positioned above the floor 12 a distance at least equal to the vertical distance the support members 40, 50 travel when going from the extended position (FIG. 8a) to the retracted position (FIG. 8c). The brackets 20, 30 may be permanently or removably attached in a pivotal manner to the arms 22, 32.

Alternatively, each bracket 20, 30 may be used to pivotally support two or more of the arms 22, 32. For example, FIGS. 1 through 9 illustrate the usage of an upper bracket 20 adapted to be attached to the wall 14 and a lower bracket 30 adapted to be attached to the wall 14 below the upper bracket 20. As another alternative, each bracket 20, 30 may be rotated 90 degrees wherein each bracket 20, 30 supports at least one of the upper arms 22 and at least one of the lower arms 32. The upper bracket 20 is preferably attached to the wall 14 in a manner that is parallel with respect to the lower bracket 30 as illustrated in FIG. 9 of the drawings.

As further shown in FIGS. 1 through 9, the upper bracket 20 and the lower bracket 30 each have a U-shaped structure with an elongated flat brace adjacent to and attached to the wall 14 with end portions that extend outwardly away from the wall 14 to pivotally connect to the arms 22, 32. The end portions of the brackets 20, 30 preferably extend outwardly from the elongated flat brace at 90 degrees. The length of the flat brace portion of the upper bracket 20 and the lower bracket 30 is preferably approximately 48 inches or greater to provide sufficient spacing between the support members 40, 50 while providing for secure attachment to studs in the wall 14 which are typically spaced apart at 16 inches. Various other shapes and structures may be utilized for the brackets 20, 30 that are capable of pivotally supporting the arms 22, 32. The flat brace portion is preferably constructed of a flat metal bar (e.g. a 3/8 inch thick steel flat bar) to allow the support members 40, 50 to get near or adjacent to the surface of the wall 14 when in the retracted position.

The end portions of the brackets 20, 30 preferably include an extended portion that extends downwardly and forwardly for pivotally connecting to an end of the corresponding actuator 24, 34 to be offset from the corresponding arms 22, 32 thereby allowing the actuators 24, 34 to provide an offsetting force to the arms 22, 32 during the entire range of movement of the arms 22, 32 from the extended position to the retracted position as best illustrated in FIGS. 8a through 8c of the drawings.

The upper bracket 20 pivotally supports a pair of upper arms 22 and the lower bracket 30 pivotally supports a pair of lower arms 32 as shown in FIGS. 1 and 2 of the drawings. The upper arms 22 preferably have a concentric pivot point on the upper bracket 20 and on the support members 40, 50. The lower arms 32 also preferably have a concentric pivot

5

point on the lower bracket **30** and on the support members **40, 50** which is positioned below the pivot point of the upper arms **22**.

It is preferable that the upper arms **22** are pivotally attached to an upper end portion of the support members **40, 50** to provide increased stability to the support members **40, 50** during use. The lower arms **32** are pivotally attached to the lower portion of the support members **40, 50** at a height approximately equal to the height the lower arms **32** are pivotally attached to the wall **14** so that the lower arms **32** extend substantially horizontal when the invention is in the extended position as best illustrated in FIG. **8a** of the drawings. The upper arms **22** are pivotally attached to the wall **14** and to the upper end portion of the support members **40, 50** such that the upper arms **22** are substantially horizontal or angled slightly downwardly from the wall **14** (e.g. 5 degrees or less) when the invention is in the extended position as further illustrated in FIG. **8a** of the drawings.

It is preferable that the upper arms **22** are parallel to the lower arms **32** when the invention is in the extended position as illustrated in FIG. **8a** of the drawings. It is further preferable that the upper arms **22** are parallel to the lower arms **32** when in the retracted position as illustrated in FIG. **8c** of the drawings. It is also further preferable that the upper arms **22** are parallel to the lower arms **32** at all locations from the extended position to the retracted position and between the respective positions as illustrated in FIGS. **8a** through **8c** of the drawings. The arms **22, 32** are preferably parallel with one another at all times in all positions of the supports members **40, 50**.

C. Support Members.

The retractable wall mounted exercise rack includes a first support member **40** and a second support member **50**. The support members **40, 50** further provide an adjustable support for a barbell **16**. The support members **40, 50** also provide support for one or more pull-up bars. The support members **40, 50** are each comprised of an elongated and preferably straight structure having a lower end and an upper end.

The second support member **50** is distally spaced apart from the first support member **40** to provide a space for the user exercising to position their body. The support members **40, 50** are preferably distally spaced apart approximately 48 inches or less. The spacing between the support members **40, 50** is preferably less than the length of the brackets **20, 30** as illustrated in FIG. **10** of the drawings, however, the spacing may be equal to or greater than the length of the brackets **20, 30**.

The support members **40, 50** preferably have the same length but may differ in length from one another. The length of the support members **40, 50** is preferably 7.5 feet or 8 feet when utilized as a combination pull-up rack and squat rack. The length of the support members **40, 50** may be shorter for the alternative embodiment comprised of just a squat rack such as 6 feet as illustrated in FIG. **11** of the drawings.

The support members **40, 50** are preferably constructed of square tubing (e.g. 2"x2", 3"x3", 4"x4") but may also be constructed of rectangular tubing (e.g. 2"x3", 3"x4"). The support members **40, 50** are preferably tubular, but may be constructed of a solid material (e.g. a metal rod) or a shaped material (e.g. U-shaped cross section). The support members **40, 50** are preferably constructed of a metal material sufficient in strength to provide support for a weighted barbell **16** having a weight of 600 pounds or more. It is also important that the support members **40, 50** are tubular to provide the strength needed to support a weighted barbell **16** while providing a relatively lightweight structure that may be

6

lifted upwardly into the retracted position by the user without significant physical effort.

The first support member **40** is parallel with respect to the second support member **50** as illustrated in FIGS. **1** through **11** of the drawings. The support members **40, 50** are further substantially parallel with respect to the wall **14** in both the extended position and the retracted position (and the positions between thereof) as illustrated in FIGS. **8a** through **8c** of the drawings. The first support member **40** and the second support member **50** are vertically orientated when in the extended position, the retracted position and in all positions between the extended position and the retracted position as shown in FIGS. **8a** through **8d** of the drawings.

The lower ends of the support members **40, 50** engage a floor **12** when in the extended position and are distally spaced above the floor **12** when in the retracted position as illustrated in FIGS. **8a** through **8d** of the drawings. The lower ends of the support members **40, 50** preferably include a first end cap **46** and a second end cap **56** respectively. The end caps **46, 56** are comprised of a material softer than the support members **40, 50** to prevent damage to the floor **12** and reduce movement during use such as, but not limited to, plastic or rubber. The end caps **46, 56** are preferably inserted into the lower opening within the lower end of the support members **40, 50** and overlap the lower edges of the support members **40, 50**. It is preferable that the lower ends of the support members **40, 50** are not attached to the floor **12** to allow for free upward movement by the user when desired.

The first support member **40** and the second support member **50** each include a plurality of first apertures **42** and a plurality of second apertures **52** respectively adapted to removably receive a first support bracket **44** and a second support bracket **54**. The support brackets **44, 54** may be comprised of various types of bar catchers such as, but not limited to, a J-cup (a.k.a. a J-hook) commonly utilized with conventional squat racks to removably receive and support a barbell **16** as illustrated in FIGS. **1** through **11** of the drawings. The support brackets **44, 54** have a pin that removably inserts into a selected aperture **42, 52** at a selected height along the support members **40, 50** based on the height of the user and/or the type of exercise being performed. The front portion of the support brackets **44, 54** includes a hook structure that supports the barbell **16** in a stationary position with respect to the support members **40, 50**. The support brackets **44, 54** further include an L-shaped structure that extends around and behind the support members **40, 50** to prevent accidental removal of the support brackets **44, 54** during an exercise.

As discussed previously, the support members **40, 50** have an extended position (e.g. see FIG. **8a**) and a retracted position (e.g. see FIG. **8c**). The support members **40, 50** are positioned near or adjacent to the wall **14** when in the retracted position and the support members **40, 50** are distally positioned away from the wall **14** when in the extended position as shown in FIGS. **8a** and **8c** of the drawings. The support members **40, 50** are preferably positioned higher when in the retracted position than when in the extended position as further shown in FIGS. **8a** through **8c** of the drawings. The distance from the wall **14** to an outer surface of the support members **40, 50** is significantly less when the support members **40, 50** are in the retracted position than when the support members **40, 50** are in the extended position. The distance from the wall **14** to an outer surface of the support members **40, 50** is preferably less than four inches when the support members **40, 50** are in the retracted position to reduce interference with the usage of the surrounding area (e.g. parking a vehicle within a garage).

The first support member **40** may be directly connected to the second support member **50** by a cross member and/or a pull-up bar. The support members **40**, **50** may be connected together at the upper portion and/or the lower portion thereof. It is preferable not to have any direct connection between the support members **40**, **50** from the lower end to near the upper portion to prevent interference with an individual working out between the support members **40**, **50**. However, the first support member **40** may not be directly connected to the second support member **50** as illustrated in FIG. **11** of the drawings.

FIGS. **1** through **10** illustrate a first pull-up bar **60** connected between upper portions of the first support member **40** and the second support member **50** by a first side support **64** and a second side support **66**. The height of the first pull-up bar **60** may be adjusted by securing the side supports **64**, **66** to various heights along the support members **40**, **50**. In addition, a second pull-up bar **62** may be connected between the support members **40**, **50** at a level below or above the first pull-up bar **60**. The second pull-up bar **62** is connected directly between the support members **40**, **50** as illustrated in FIGS. **1** through **6** of the drawings. It can be appreciated that only a single pull-up bar may be connected between the support members **40**, **50** either directly such as the second pull-up bar **62** or indirectly with the side supports **64**, **66** such as the first pull-up bar **60**. The pull-up bars **60**, **62** may have various widths such as, but not limited to, 42 inches.

D. Arms.

A first set of arms **22**, **32** are pivotally connected to the first support member **40** which are adapted to be pivotally connected to the wall **14** opposite of the first support member **40**. It is preferable that the first set of arms **22**, **32** is pivotally connected to one or more brackets **20**, **30** attached to the wall **14** as illustrated in FIGS. **1** through **11** of the drawings. The arms **22**, **32** are preferably comprised of a flat metal bar.

A second set of arms **22**, **32** are pivotally connected to the second support member **50** which are adapted to be pivotally connected to the wall **14** opposite of the second support member **50**. It is preferable that the second set of arms **22**, **32** is pivotally connected to one or more brackets **20**, **30** attached to the wall **14** as illustrated in FIGS. **1** through **11** of the drawings.

The first set of arms **22**, **32** and the second set of arms **22**, **32** each preferably have the same length to provide for a constant vertical support of the support members **40**, **50** and parallel with respect to the wall **14** in all positions as illustrated in FIGS. **8a** through **8b** of the drawings. However, varying lengths for the arms **22**, **32** may be utilized where the support members **40**, **50** are not parallel with respect to the wall **14**.

The first set of arms is preferably comprised of at least one upper arm **22** pivotally connected to the upper bracket **20** and at least one lower arm **32** pivotally connected to the lower bracket **30** as illustrated in FIGS. **1** through **4** of the drawings. The second set of arms is preferably comprised of at least one upper arm **22** pivotally connected to the upper bracket **20** and at least one lower arm **32** pivotally connected to the lower bracket **30** as illustrated in FIGS. **1** through **4** of the drawings. It is further preferable that two upper arms **22** are used to support the upper portion of the support members **40**, **50** and two lower arms **32** are used to support the middle or lower portion of the support members **40**, **50**. Additional sets of arms may be used in addition to what is

illustrated in the drawings (e.g. a pair of middle arms could be connected to a middle bracket between the upper arms **22** and the lower arms **32**).

E. Actuators.

At least one actuator **24**, **34** is pivotally connected to one of the arms **22**, **32** at a first end and is pivotally connected to the wall **14** at a second end. The actuator **24**, **34** may be directly connected to the wall **14** or to one of the brackets **20**, **30**. The actuator **24**, **34** applies an upward biasing force to the respective arm **22**, **32** to assist in lifting the first support member **40** upwardly into the retracted position. The second support member **50** includes at least one corresponding actuator **24**, **34** to assist in lifting the second support member **50** as illustrated in FIGS. **1** through **4** of the drawings.

The actuator **24**, **34** is connected to the wall **14** in a manner offset from the pivot location of the respective arm **22**, **32** as illustrated in FIGS. **8a** through **8d** of the drawings. The actuator **24**, **34** is preferably pivotally connected to the wall **14** at a pivot axis that is forward and downward from the pivot axis of the corresponding arm **22**, **32** pivotally connected to the wall **14** to provide an upward lifting force to the corresponding arm **22**, **32** throughout the entire range of positions as best illustrated in FIGS. **8a** through **8d** of the drawings. The pivot axis of the actuator **24**, **34** is preferably not concentric with the pivot axis of the corresponding arm **22**, **32**. The actuator **24**, **34** preferably is connected centrally to the respective arm **22**, **32** as illustrated in FIGS. **1**, **2**, **7** through **8d** of the drawings.

As illustrated in FIGS. **1** through **4** of the drawings, each upper arm **22** preferably includes a corresponding upper actuator **24** connected between the upper bracket **20** and the upper arm **22**. In addition, each lower arm **32** preferably includes a corresponding lower actuator **34** connected between the lower bracket **30** and the lower arm **32**. Depending upon the force applied to the arms **22**, **32** by the actuator **24**, **34** and the weight of the support members **40**, **50**, a greater or less number of actuators **24**, **34** may be used. For example, if larger actuators are used, only at least one upper actuator **24** or at least one lower actuator **34** may be needed. Alternatively, only a single actuator **24**, **34** may be used connected to a single arm **22**, **32** if sufficient force is applied. However, it is preferable to have at least one actuator **24**, **34** for each of the support members **40**, **50** to prevent an off-balance countering force being applied to the support members **40**, **50**.

The actuators **24**, **34** are preferably comprised of linear actuators. Examples of suitable linear actuators include, but are not limited to, gas actuators, gas springs, pneumatic actuators, hydraulic actuators, hydraulic gas lift support arms, spring actuators, mechanical compression struts, compression actuators, dampers and the like. The actuators **24**, **34** may also be rotary actuators such as, but not limited to, torsion springs, coil springs and the like. The actuators **24**, **34** may be motorized such as an electro-mechanical actuator or servomotor actuator to lift the retractable wall mounted exercise rack from the extended position to the retracted position without the user having to lift the structure. In addition, a ratchet system may be connected to the arms **22**, **32** to prevent the rack system **10** from lowering during a lifting procedure.

F. Locking System.

The retractable wall mounted exercise rack preferably includes a locking system that allows for selectively locking the retractable wall mounted exercise rack system **10** into the retracted position. The user is able to selectively lock the

invention to prevent the structure from accidentally falling downwardly into the extended position which could injure a child or damage a vehicle.

A first locking aperture 26 extends within and through at least one of the upper arms 22 as illustrated in FIGS. 1 and 2 of the drawings. A first receiver aperture 43 extends within and through at least one of the support members 40, 50. The first locking aperture 26 is aligned with the first receiver aperture 43 when the corresponding support member 40, 50 is in the retracted position to removably receive a first locking pin 48 as illustrated in FIGS. 3 and 4 of the drawings. The first locking pin 48 extends through the first locking aperture 26 and the first receiver aperture 43 to lock the corresponding support member in the retracted position. A first clip 49 may be removably inserted through a hole within the distal portion of the first locking pin 48 to prevent accidental removal of the first locking pin 48.

A second locking aperture 36 extends within and through at least one of the lower arms 32 as illustrated in FIGS. 1 and 2 of the drawings. A second receiver aperture 53 extends within and through at least one of the support members 40, 50. The second locking aperture 36 is aligned with the second receiver aperture 53 when the corresponding support member 40, 50 is in the retracted position to removably receive a second locking pin 58 as illustrated in FIGS. 3 and 4 of the drawings. The second locking pin 58 extends through the second locking aperture 36 and the second receiver aperture 53 to lock the corresponding support member 40, 50 in the retracted position. A second clip 59 may be removably inserted through a hole within the distal portion of the second locking pin 58 to prevent accidental removal of the second locking pin 58. The clips 49, 59 may be comprised of any clip such as, but not limited to, a hitch pin clip.

G. Operation of Preferred Embodiment.

In use, the upper bracket 20 and the lower bracket 30 are mounted to the wall 14 as illustrated in FIGS. 8a through 10 of the drawings. The retractable wall mounted exercise rack system 10 is then lowered into the extended position as illustrated in FIGS. 1, 2 and 8a of the drawings. The rack system 10 is pulled outwardly and lowered until the lower ends of the support members 40, 50 engage and are supported substantially by the floor 12 as best illustrated in FIG. 8a of the drawings. With the rack system 10 in the extended position, the user is able to perform the exercise of their choice such as, but not limited to, pull-ups, squats, bench presses and the like. The user may also adjust the desired position of the support brackets 44, 54 to support the barbell 16 at the desired height.

When the user is finished exercising, they remove the barbell 16 and lift upon the support members 40, 50 thereby causing the support members 40, 50 to lift upwardly and inwardly as illustrated in FIG. 8b of the drawings. The actuators 24, 34 provide assistance to the user by lifting upwardly upon the corresponding arms 22, 32 thereby reducing the amount of weight the user must lift. The support members 40, 50 are continued upwardly and inwardly until they engage the brackets 20, 30 and are near (or adjacent) to the wall 14 as illustrated in FIG. 8c of the drawings. The actuators 24, 34 are able to maintain the rack system 10 in the retracted position because there is little vertical force being applied to the actuators 24, 34 because of the substantially vertically aligned arms 22, 32 and support members 40, 50 as illustrated in FIG. 8c. However, to ensure that a child doesn't accidentally pull downwardly upon the rack system 10 causing a force that overcomes the actuators 24, 34, the user preferably inserts at least one

locking pin 48, 58 through one of the locking apertures 26, 36 and corresponding receiver apertures 43, 53 to prevent the rack system 10 from being removed from the retracted position. At least one locking pin 48, 58 for each of the support arms are preferably utilized. When the user desires to use the rack system 10 again for exercise, they simply remove the locking pins 48, 58 and then pull downwardly and outwardly upon the support members 40, 50 thereby causing the rack system 10 to fall downwardly and outwardly into the extended position as illustrated in FIG. 8a of the drawings. The above process is then simply repeated for the continued life of the rack system 10.

Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although methods and materials similar to or equivalent to those described herein can be used in the practice or testing of the retractable wall mounted exercise rack, suitable methods and materials are described above. All publications, patent applications, patents, and other references mentioned herein are incorporated by reference in their entirety to the extent allowed by applicable law and regulations. The retractable wall mounted exercise rack may be embodied in other specific forms without departing from the spirit or essential attributes thereof, and it is therefore desired that the present embodiment be considered in all respects as illustrative and not restrictive. Any headings utilized within the description are for convenience only and have no legal or limiting effect.

What is claimed is:

1. A wall mountable exercise rack, comprising:
 - a main bracket adapted to be connected to a wall, wherein the bracket is comprised of an elongated brace, a first bracket connected to the elongated brace and a second bracket connected to the elongated brace, wherein the first bracket and the second bracket are perpendicular to the elongated brace;
 - a first support member;
 - a first upper arm connected to an upper portion of the first support member, wherein the first upper arm extends in a first direction from the first support member and is connected to the first bracket;
 - a second support member spaced apart from the first support member;
 - a second bracket;
 - a second upper arm connected to an upper portion of the second support member, wherein the second upper arm extends in the first direction from the second support member and is connected to the second bracket;
 - wherein the first support member and the second support member are substantially vertically orientated and substantially parallel to one another;
 - wherein the first support member has a lower end and the second support member has a lower end, wherein the lower end of the first support member and the lower end of the second support member each are adapted to engage a floor;
 - wherein the first support member includes a plurality of first apertures adapted to removably receive a first support bracket and wherein the second support member includes a plurality of second apertures adapted to removably receive a second support bracket, wherein the first support bracket and the second support bracket are configured to removably receive and support a barbell;
 - a first side support member connected to the upper portion of the first support member, wherein the first side

11

support member extends in a second direction from the first support member, wherein the second direction is opposite of the first direction;

a second side support member connected to the upper portion of the second support member, wherein the second side support member extends in a second direction from the first support member; and

a pull-up bar connected between the distal portions of the first side support member and the second side support member, wherein the pull-up bar is positioned outwardly away from the first support member and the second support member.

2. The wall mountable exercise rack of claim 1, wherein the first side support member is parallel to the second side support member.

3. The wall mountable exercise rack of claim 1, wherein the first side support member has the same length as the second side support member.

4. The wall mountable exercise rack of claim 1, wherein the height of the pull-up bar is adjustable.

5. The wall mountable exercise rack of claim 4, wherein the first side support member and the second side support member are adjustably secured to the first support member and the second support member respectively.

6. The wall mountable exercise rack of claim 1, wherein the pull-up bar has a width of 42 inches.

7. The wall mountable exercise rack of claim 1, wherein the first side support member and the second side support member are parallel with respect to the first upper arm and the second upper arm.

8. The wall mountable exercise rack of claim 1, wherein the first upper arm is pivotally connected to the first support member and is adapted to be pivotally connected to the wall, and wherein the second upper arm is pivotally connected to the second support member and adapted to be pivotally connected to the wall.

9. The wall mountable exercise rack of claim 1, wherein the first bracket, the second bracket, and the elongate brace form a unitary bracket structure.

10. The wall mountable exercise rack of claim 9, wherein the unitary bracket structure has a U-shaped structure.

11. The wall mountable exercise rack of claim 9, wherein the elongated brace is an elongated flat brace and adapted to be positioned adjacent to and attached to the wall.

12. The wall mountable exercise rack of claim 11, wherein the unitary bracket structure includes a first end portion and a second end portion that extend outwardly from the elongated flat brace, wherein the first upper arm is connected to the first end portion and wherein the second upper arm is connected to the second end portion.

13. The wall mountable exercise rack of claim 12, wherein the first end portion and the second end portion extend outwardly from the elongated flat brace at 90 degrees.

14. The wall mountable exercise rack of claim 12, wherein the first upper arm is pivotally connected to the first end portion and wherein the second upper arm is pivotally connected to the second end portion.

15. The wall mountable exercise rack of claim 11, wherein the elongated flat brace includes a plurality of apertures that are adapted to receive corresponding threaded fasteners that extend into the wall.

16. The wall mountable exercise rack of claim 15, wherein the plurality of apertures are slotted.

17. The wall mountable exercise rack of claim 1, including a second pull-up bar connected between the first support member and the second support member.

12

18. The wall mountable exercise rack of claim 1, wherein the first upper arm is pivotally connected to the first bracket and wherein the second upper arm is pivotally connected to the second bracket.

19. The wall mountable exercise rack of claim 1, including:

a first lower arm connected to a lower portion of the first support member, wherein the first lower arm extends in the first direction from the first support member, and wherein the first lower arm is adapted to be connected to the wall by a third bracket; and

a second lower arm connected to a lower portion of the second support member, wherein the second lower arm extends in the first direction from the second support member, and wherein the second lower arm is adapted to be connected to the wall by a fourth bracket.

20. The wall mountable exercise rack of claim 1, wherein the first side support member extends upwardly from the first support member and the second side support member extends upwardly from the second support member.

21. The wall mountable exercise rack of claim 1, wherein the first side support member and the second side support member are each comprised of a first segment and a second segment, wherein the first segment extends substantially horizontally in the second direction and wherein the second segment extends upwardly to the first segment.

22. The wall mountable exercise rack of claim 1, wherein the first side support member and the second side support member each have a V-shape.

23. A wall mountable exercise rack, comprising:

a wall;

a main bracket connected to the wall, wherein the bracket is comprised of an elongated brace, a first bracket connected to the elongated brace and a second bracket connected to the elongated brace, wherein the first bracket and the second bracket are perpendicular to the elongated brace;

a first support member;

a first upper arm connected to an upper portion of the first support member, wherein the first upper arm extends in a first direction from the first support member and is connected to the first bracket;

a second support member spaced apart from the first support member;

a second bracket;

a second upper arm connected to an upper portion of the second support member, wherein the second upper arm extends in the first direction from the second support member and is connected to the second bracket;

wherein the first support member and the second support member are substantially vertically orientated and substantially parallel to one another;

wherein the first support member has a lower end and the second support member has a lower end, wherein the lower end of the first support member and the lower end of the second support member each are adapted to engage a floor;

wherein the first support member includes a plurality of first apertures adapted to removably receive a first support bracket and wherein the second support member includes a plurality of second apertures adapted to removably receive a second support bracket, wherein the first support bracket and the second support bracket are configured to removably receive and support a barbell;

a first side support member connected to the upper portion of the first support member, wherein the first side

13

support member extends in a second direction from the first support member, wherein the second direction is opposite of the first direction;

a second side support member connected to the upper portion of the second support member, wherein the second side support member extends in a second direction from the first support member; and

a pull-up bar connected between the distal portions of the first side support member and the second side support member, wherein the pull-up bar is positioned outwardly away from the first support member and the second support member.

24. A wall mountable exercise rack, comprising:

a main bracket connected to the wall, wherein the bracket is comprised of an elongated brace, a first bracket connected to the elongated brace and a second bracket connected to the elongated brace, wherein the first bracket and the second bracket are perpendicular to the elongated brace;

a first support member, wherein the first support member is comprised of square tubing or rectangular tubing, and wherein the first support member is comprised of a metal material;

a first upper arm connected to an upper portion of the first support member, wherein the first upper arm extends in a first direction from the first support member, and wherein the first upper arm is connected to the first bracket;

wherein the first bracket is configured to extend outwardly from the wall at 90 degrees;

a second support member spaced apart from the first support member, wherein the first support member is comprised of square tubing or rectangular tubing, and wherein the first support member is comprised of a metal material;

a second upper arm connected to an upper portion of the second support member, wherein the second upper arm extends in the first direction from the second support

14

member, and wherein the second upper arm is connected to the second bracket;

wherein the second bracket is configured to extend outwardly from the wall at 90 degrees;

wherein the first support member and the second support member are substantially vertically orientated and substantially parallel to one another;

wherein the first support member has a lower end and the second support member has a lower end, wherein the lower end of the first support member and the lower end of the second support member each are adapted to engage a floor;

wherein the first support member includes a plurality of first apertures adapted to removably receive a first support bracket and wherein the second support member includes a plurality of second apertures adapted to removably receive a second support bracket, wherein the first support bracket and the second support bracket are configured to removably receive and support a barbell;

a first side support member connected to the upper portion of the first support member, wherein the first side support member extends in a second direction from the first support member, wherein the second direction is opposite of the first direction;

a second side support member connected to the upper portion of the second support member, wherein the second side support member extends in a second direction from the first support member; and

a pull-up bar connected between the distal portions of the first side support member and the second side support member, wherein the pull-up bar is positioned outwardly away from the first support member and the second support member;

wherein the first side support member is parallel to the second side support member;

wherein the first side support member has the same length as the second side support member.

* * * * *